

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets".



element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[SRGP400100](#)

[SRGP400200](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant

Surface mount encoder with 1.55mm height $\phi 9.23\text{mm}$ contribute in space saving

Hollow Shaft
Type Devices



Typical Specifications

Items		Specifications
Rating(max.)(min.) (Resistive load)		1mA 5V DC/50 μ A 3V DC
Output voltage		1V max. at 1mA 5V DC (Resistive load)
Operating life	Without resistor	100,000cycles
	With resistor	100,000cycles


Product Line

Detent torque (mN·m)	Number of detent	Number of pulse	Soldering	Minimum order unit (pcs.)	Product No.
2 $\pm$ 1	24	12	Reflow	3,200	SRGP400100
3.5 $\pm$ 1					SRGP400200

Taping Specification (Taping Packaging)

Reel Size

Unit:mm



Number of packages(pcs.)			Tape width (mm)
1 reel	1 case / Japan	1 case / export packing	
800	1,600	3,200	32

Encoder
Type

Potentiometer
Type

Note


Order products in N minimum order units (1 reel or 1 case).

Dimensions

Unit:mm

Style	Recommended pattern for reflow (All tolerance shall be ± 0.05)
Ground term. Phase difference of code portion (30°) CW (15°) CCW Detent position ON OFF ON OFF T1, T3 = 1/4T $\pm$ 1/8T T2, T4 = Phase difference shall not be reverse	

List of Varieties

Type		Hollow type				
		17mm size		22mm size	30mm size	
Series		SRGP30	SRGP40	SRGP20	SRGPWJ	
Photo						
Output		Incremental				
Outline specifications	Shaft types	Hollow shaft				
	Operating direction	Vertical				
	Number of pulse/ Number of detent	9/18	12/24	10/20	16/16 16/32	
	Push switch (Travel mm)	Without				
	Optional functions					
	Changeover angle	20°	15°	18°	22.5 °	
Dimensions (mm)	W	17.5		23.6	31.8	
	D	18.5	18.25	23	32	
	H	2.3	1.55	4.5		
Soldering	Manual soldering	350 ± 5 , 3s max.	350 ± 10 , 3 ± 1s max.	350 ± 10 , 3 ± 1s		
	Dip soldering			260 ± 5 , 5 ± 1s		
	Reflow soldering	Please see P.198				
Maximum operating current(Resistive load)		-10 to +60		-40 to +85		
Electrical performance	Output wave	1V max. at 5V DC,1mA (resistive load) 				
	Insulation resistance	100MΩ min. 100V DC				
	Voltage proof	100V AC for 1minute				
Mechanical performance	Rotational torque	5 ± 2.5mN·m	2 ± 1mN·m	7 ± 3mN·m	13 ± 4mN·m	
			3.5 ± 1mN·m		6.5 ± 4mN·m	
	Terminal strength			5N for 1minute		
	Actuator strength	Rotational direction	20N		40N	
		Push direction				
Vibration	10 to 55 to 10Hz/min., the amplitude is 1.5mm for all the frequencies, in the 3 direction of X, Y and Z for 2 hours respectively					
Environmental performance	Cold	-40 ± 2 for 96h	-20 ± 2 for 96h			
	Dry heat	85 ± 2 for 96h				
	Damp heat	40 ± 2 , 90 to 95%RH for 96h				
Page		450	451	452		

Hollow Shaft
Type DevicesEncoder
TypePotentiometer
Type


Note

※ The operating temperature range for automotive applications can be raised upon request. Please contact us for requirements of this kind.

Soldering Conditions

Example of Reflow Soldering Condition

- 1. Heating method: Double heating method with infrared heater.
- 2. Temperature measurement: Thermocouple 0.1 to 0.2 φ CA(K)or CC(T)at soldering portion(copper foil surface). A heat resisting tape should be used for fixed measurement.
- 3. Temperature profile



Series(Reflow type)	A() Max	B()	C(s)	D()	E()	F(s)
SRGP30	240	230	20	150	150	120
SRGP40	260		40	180		

Notes

- 1. The condition mentioned above is the temperature on the mounting surface of a PC board. There are cases where the PC board's temperature greatly differs from that of the switch, depending on the PC board's material, size, thickness, etc. The above-stated conditions shall also apply to switch surface temperatures.
- 2. Soldering conditions differ depending on reflow soldering machines. You are requested to verify the soldering conditions thoroughly beforehand.



element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[SRGP400100](#)

[SRGP400200](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant