


## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets".

### PACKAGE DIMENSIONS



#### NOTES:


1. Dimensions for all drawings are in inches (mm).
2. Tolerance of  $\pm .010$  (.25) on all non-nominal dimensions unless otherwise specified.

### DESCRIPTION


- The F5D series is a 880 nm LED in a narrow angle, TO-46 package.

### FEATURES

- Good optical to mechanical alignment
- Mechanically and wavelength matched to the TO-18 series phototransistor
- Hermetically sealed package
- High irradiance level



### SCHEMATIC



1. Derate power dissipation linearly 1.70 mW/°C above 25°C ambient.
2. Derate power dissipation linearly 13.0 mW/°C above 25°C case.
3. RMA flux is recommended.
4. Methanol or isopropyl alcohols are recommended as cleaning agents.
5. Soldering iron tip 1/16" (1.6mm) minimum from housing.
6. As long as leads are not under any stress or spring tension
7. Total power output,  $P_O$ , is the total power radiated by the device into a solid angle of  $2\pi$  steradians.

### ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Rating	Unit
Operating Temperature	$T_{OPR}$	-65 to +125	°C
Storage Temperature	$T_{STG}$	-65 to +150	°C
Soldering Temperature (Iron) <sup>(3,4,5 and 6)</sup>	$T_{SOL-I}$	240 for 5 sec	°C
Soldering Temperature (Flow) <sup>(3,4 and 6)</sup>	$T_{SOL-F}$	260 for 10 sec	°C
Continuous Forward Current	$I_F$	100	mA
Forward Current (pw, 10µs; 100Hz)	$I_F$	3	A
Forward Current (pw, 1µs; 200Hz)	$I_F$	10	A
Reverse Voltage	$V_R$	3	V
Power Dissipation ( $T_A = 25^\circ\text{C}$ ) <sup>(1)</sup>	$P_D$	170	mW
Power Dissipation ( $T_C = 25^\circ\text{C}$ ) <sup>(2)</sup>	$P_D$	1.3	W

### ELECTRICAL / OPTICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ ) (All measurements made under pulse conditions)

PARAMETER	TEST CONDITIONS	SYMBOL	MIN	TYP	MAX	UNITS
Peak Emission Wavelength	$I_F = 100$ mA	$\lambda_P$	—	880	—	nm
Emission Angle at 1/2 Power	$I_F = 100$ mA	$\theta$	—	$\pm 8$	—	Deg.
Forward Voltage	$I_F = 100$ mA	$V_F$	—	—	1.7	V
Reverse Leakage Current	$V_R = 3$ V	$I_R$	—	—	10	µA
Total Power F5D1 <sup>(7)</sup>	$I_F = 100$ mA	$P_O$	12.0	—	—	mW
Total Power F5D2 <sup>(7)</sup>	$I_F = 100$ mA	$P_O$	9.0	—	—	mW
Total Power F5D3 <sup>(7)</sup>	$I_F = 100$ mA	$P_O$	10.5	—	—	mW
Rise Time 0-90% of output		$t_r$	—	1.5	—	µs
Fall Time 100-10% of output		$t_f$	—	1.5	—	µs

Figure 1. Power Output vs. Input Current




Figure 2. Power Output vs. Temperature




Figure 3. Forward Voltage vs. Temperature




Figure 4. Typical Radiation Pattern




Figure 5. Output vs. Input with L14G Detector





Figure 6. Output vs. Wavelength



### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.